



# LATCH CLAMPS HORIZONTAL & VERTICAL

#### • Features:

Latch clamps are available in two configurations; horizontal, with the clamp and latch bracket in the same plane (LU200H, LU400H, LU700H, LU2000H and LU4000H) or a vertical (corner) configuration, the clamp and bracket being at right angles to each other (LU200V, LU400V, and LU700V).

All latch clamps are fitted with PVC handle grips.

#### Specification:

The components of both variants of LU200, LU400 and LU700 clamps are of zinc plated and passivated steel, the rivet being of stainless steel and rotating in the close-toleranced hole of hardened parts or in hardened bushes. The handle and the trunnion which holds the 'U'-bolt are also hardened to resist wear.

Clamps LU2000H and LU4000H have precision cast steel bases and latch brackets and handles of S.G. iron.

#### Installation:

It is important that the clamp and latch bracket of horizontal (H) variants are in alignment when viewed from both the top and the side to ensure that the clamp locks over centre correctly.

Vertical (V) variants should be in alignment when viewed from the top, and, when viewed from the side, the base of the latch bracket should be aligned with the flat front edge of the clamp base and at right angles to it.

The 'U' bolt should be adjusted to ensure an equal pull on either side.



HORIZONTAL
MODEL LU200H



**Nominal Holding Force:** 


200 daN

0.05 Kg

Supplied complete with

Latch Bracket as shown.

See "Features and installation information" page for installation instructions.



## HORIZONTAL MODEL LU200HSS





Iominal Holding Force:

200 daN

0.05 Kg


Supplied complete with:

Latch Bracket as shown.

Material:

BS 304 S15.

See "Features and installation information" page for installation instructions.



### HORIZONTAL MODEL LU400H



#### **Nominal Holding Force:**


400 daN

Weight

Supplied complete with

Latch Bracket as shown.

See "Features and installation information" page for installation instructions.



TELEPHONE: 00 44 (0)1908 374022 FAX: 00 44 (0)1908 641628



HORIZONTAL
MODEL LU400HSS





**Nominal Holding Force:** 

400 daN


0.25 Kg

Supplied complete with:

Latch Bracket as shown.

Material: BS 304 S15.

See "Features and installation information" page for installation instructions.



# HORIZONTAL MODEL LU700H



Nominal Holding Force:

700 daN


Weight: 0.70 Kg

0.70 kg

Latch Bracket as shown.

Cas "Factures and installati

See "Features and installation information" page for installation instructions.



### HORIZONTAL MODEL LU700HSS





#### Nominal Holding Force:

700 daN

Weight:


Supplied complete with:

Latch Bracket as shown.

Material:

BS 304 S15.

See "Features and installation information" page for installation instructions.




TELEPHONE: 00 44 (0)1908 374022 FAX: 00 44 (0)1908 641628

E-Mail: sales@brauer.co.uk www.brauer.co.uk


# **BRAUER**<sup>®</sup>

### **LATCH CLAMPS**

# HORIZONTAL MODEL LU2000H



# HORIZONTAL MODEL LU4000H



TELEPHONE: 00 44 (0)1908 374022 FAX: 00 44 (0)1908 641628



### **VERTICAL** MODEL **LU200V**




**Nominal Holding Force:** 

200 daN

0.05 Kg

Latch Bracket as shown.

See "Features and installation information" page for installation instructions.



### **VERTICAL** MODEL LU200VSS





inal Holding Force:


200 daN

0.05 Kg

Latch Bracket as shown.

BS 304 S15.

See "Features and installation information" page for installation instructions.



#### **VERTICAL** MODEL **LU400V**




#### **Nominal Holding Force:**

400 daN

Latch Bracket as shown.

See "Features and installation information" page for installation instructions.



TELEPHONE: 00 44 (0)1908 374022 FAX: 00 44 (0)1908 641628

E-Mail: sales@brauer.co.uk www.brauer.co.uk



### **VERTICAL** MODEL **LU400VSS**





**Nominal Holding Force:** 


400 daN

0.25 Kg

Latch Bracket as shown.

BS 304 S15.

See "Features and installation information" page for installation instructions.



**VERTICAL** MODEL **LU700V** 




nal Holding Force:

700 daN

0.70 Kg

Latch Bracket as shown.

See "Features and installation information" page for installation instructions.



**VERTICAL** MODEL LU700VSS





Nominal Holding Force:


700 daN

Supplied complete with:

Latch Bracket as shown.

BS 304 S15.

See "Features and installation information" page for installation instructions.



TELEPHONE: 00 44 (0)1908 374022 FAX: 00 44 (0)1908 641628

E-Mail: sales@brauer.co.uk www.brauer.co.uk